



T17 Specifications | Heavy-Duty High Performance Battery Rider Scrubber

SCRUBBING SYSTEM

Cleaning path	40 in 1,015 mm
With scrubbing side brush	52 in 1,320 mm
With RH sweeping side brush (cyl scrub only)	46 in 1,165 mm
With Dual sweeping side brush (cyl scrub only)	52 in 1,320 mm
Sweeping with Presweep	49.4 in 1,255 mm

Cylindrical main brushes

Brush speed	500 rpm
Brush diameter (2)	9 in 230 mm
Brush down force (up to)	550 lb 250 kg
Brush motors-brushless (2)	1.5 hp 1.125 kW
Motor rating	IP44
Debris hopper	0.7 ft ³ 20 L

Disk main brushes

Brush speed	315 rpm
Brush size diameter (2)	20 in 510 mm
Brush down force (up to)	550 lb 250 kg
Brush motor-brushless (2)	1.5 hp 1.125 kW
Motor rating	IP44

Optional Presweep

Debris capacity (overall)	1.3 ft ³ 37 L
Filter bag capacity	1.0 ft ³ 28 L

Tanks

Solution tank	75 gal 285 L
Solution capacity (ES [®])	115 gal 435 L
Recovery tank	91.1 gal 346 L
Demisting chamber	16.1 gal 61 L
Vacuum fan (Dual)	2 x 0.8 hp 2 x 0.6 kW
Speed	14,500 rpm
Water lift	65 in 1,650 mm

PROPELLING SYSTEM

Propel speed forward (transport variable to)	5.5 mph 9 km / h
Propel speed forward (scrubbing variable to)	4.0 mph 6.5 km / h
Propel speed reverse (variable to)	3 mph 5 km / h
Propel motor	3.0 hp 2.25 kW
Speed control	Electronic - AC
Gradeability	Base Unit w/Ramp Kit
Transport (empty for trailering)	12 deg / 21% 12 deg / 21%
Transport at gross weight	7 deg / 12% 8.5 deg / 14.8%
Working (scrubbing)	5 deg / 8.7% 6 deg / 10.5%
Ground clearance (transport)	2.5 in 64 mm
Tire front (1), non-marking	13.8 x 5.8 in 350 x 150 mm
Tires rear (2), non-marking	15 x 5 in 380 x 125 mm

BATTERY SELECTIONS (est. continuous runtime: economy mode)

Battery options	
Optional battery packages	(up to 3.5 hrs) 36V, 510 AH C/6
	(up to 5.75 hrs) 36V, 750 AH C/6
	(up to 7.5 hrs) 36V, 930 AH C/6

Battery chargers available for all optional batteries

SOUND LEVEL

Operator's ear:	
Disk: Mode #2*	65 dBA; Kpa 3 dBA
Cylindrical: Mode #2*	66 dBA; Kpa 3 dBA
*Sound pressure level tested per IEC 60335-2-72	
*Vacuum On, Squeegee Down, Brushes On, Brushes Up	

MACHINE DIMENSIONS

Length Basic Machine	87.9 in 2,230 mm
Length with Pre-Sweep	113 in 2,870 mm
Width	
Body	46 in 1,168 mm
Body (with Side Brush)	53 in 1,346 mm
Rear squeegee (hard width)	49 in 1,245 mm
Height (top of Steering Wheel)	58.25 in 1,480 mm
With overhead guard	82.5 in 2,096 mm
Weight	
Empty (Base Unit)	1,925 lb 875 kg
With standard 510 AH batteries	3,365 lb 1,525 kg
Gross Vehicle Weight (GVW)	5,940 lb 2,700 kg
Minimum aisle turn	93.25 in 2,370 mm

STANDARD FEATURES

1-Step™ One Button Scrub Operation	Onboard Diagnostics
Touch-N-Go™ Wheel Mounted Module	Wheel Mounted Horn
Recover Tank Full Indicator	Wheel Mounted Water Shut-Off
Solution Tank Empty Indicator	Full Wrap Steel Bumper
Non Marking Drive Wheel	Cushioned Stacked Corner Rollers (front)
Yellow Maintenance Touch Points	Manual Parking Brake
Recovery Tank Debris Tray	Duramer™ Tanks & Shrouds
In-Line Vacuum Fan Filter	Variable Flow Cuff Tank Drains
Swinging Rear Parabolic Squeegee	No-Tool Squeegee Change
SmartRelease™ Breakaway Rear Squeegee	No-Tool Brush Change
Underwriters Laboratory (UL [®]) E Certified	

OPTIONAL EQUIPMENT

ec-H2O™ Solution System	S.E. (Severe Environment) Switch
ES [®] Extended Scrub w/Detergent Metering	Solution Auto Fill System
Spray Hose (15 ft / 4.5 m) w/Retracting Reel	Scrubbing Side Brush
Vacuum Wand	Sweep Side Brush (RH or Dual)
Slide-Out Battery System	FOPS Certified Overhead Guard
Heavy-Duty Rear Squeegee Guard	Pre-sweep with Dry Dust Control
Deluxe Seat w/Armrests & Seatbelt	Power Steering
Headlights (LED)	AV Backup Alarm (LED)
High Traction Tire(s)	Battery Watering System
Fire Extinguisher	Underwriters Laboratory (UL [®]) Type ES Certified

WARRANTY

Please refer to your local Tennant representative for information.

For a complete selection of genuine Tennant brushes and pads, please consult the *T17 Parts and Consumables Reference Guide*.